


Weight – approx. 4.4 kg



OPTIONS

FABRIC RIBBON CARTRIDGE (BLACK)
FABRIC RIBBON PACK (BLACK)
FABRIC RIBBON CARTRIDGE (COLOUR)
FILM RIBBON CARTRIDGE (BLACK)
SINGLE BIN CUT SHEET FEEDER
PULL TRACTOR UNIT
COLOUR UPGRADE KIT
ROLL PAPER HOLDER

24-PIN NARROW CARRIAGE IMPACT PRINTER

LQ-300+II

PRINT DIRECTION			Bi-directional with logic seeking
PRINT SPEED	HIGH SPEED DRAFT	10 CPI	300 cps
	DRAFT	10/12/15 CPI	225/270/337 cps
	DRAFT CONDENSED	17/20 CPI	192/225 cps
	LQ	10/12/15 CPI	75/90/112 cps
	LQ CONDENSED	17/20 CPI	128/150 cps
PRINT CHARACTERISTICS	CHARACTER SETS	15 International character sets: 13 character code tables (Standard); Italic, PC437, PC850, PC860, PC861, PC863, PC865, Abicomp, BRAScii, Roman 8, ISO Latin 1, PC858, ISO 8859-15	
	BITMAP FONTS	Epson Draft and Courier: 10, 12, 15 CPI; Epson Roman and Sans Serif: 10, 12, 15 CPI, Proportional; Epson Prestige: 10, 12 CPI; Epson Script, OCR-B, Orator and Orator-S: 10 CPI; Epson Script C: Proportional	
	SCALABLE FONTS	Epson Roman, Sans Serif, Roman T and Sans Serif H: 10.5 pt., 8 to 32 pt. (every 2 pt.)	
PRINTABLE COLUMNS	BAR CODE FONT	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, PostNet	
	PITCH (CPI)	CHARACTER PER LINE	
	10 CPI	80	
	12 CPI	96	
	15 CPI	120	
17 CPI CONDENSED	137		
20 CPI CONDENSED	160		
PAPER HANDLING			
PAPER PATH	MANUAL INSERTION:	Rear in, Top out	
	PUSH TRACTOR:	Rear in, Top out	
	PULL TRACTOR:	Rear/Bottom in, Top out	
	CUT SHEET FEEDER:	Rear in, Top out	
PAPER SIZE			
CUT SHEET	MANUAL INSERTION	Width:	100 ~ 257 mm (3.9 ~ 10.1")
		Length:	100 ~ 364 mm (3.9 ~ 14.3")
		Thickness:	0.065 ~ 0.14 mm (0.0025 ~ 0.0055")
	CSF SINGLE-BIN	Width:	182 ~ 216 mm (7.2 ~ 8.5")
		Length:	257 ~ 356 mm (10.1 ~ 14.0")
		Thickness:	0.07 ~ 0.14 mm (0.0028 ~ 0.0055")
	MULTI PART	Width:	100 ~ 257 mm (3.9 ~ 10.1")
		Length:	100 ~ 364 mm (3.9 ~ 14.3")
		Thickness:	0.12 ~ 0.32 mm (0.0047 ~ 0.013") (Total)
ENVELOPE	No. 6	Width:	165 mm (6.5")
		Length:	92 mm (3.6")
		Thickness:	0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
	No. 10	Width:	241 mm (9.5")
		Length:	105 mm (4.1")
		Thickness:	0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
CONTINUOUS PAPER		Width:	101.6 ~ 254 mm (4.0 ~ 10.0")
		Length:	101.6 ~ 558.8 mm (4.0 ~ 22.0")
		Thickness:	0.065 ~ 0.32 mm (0.0025 ~ 0.013") (Total)
LABEL		Width:	101.6 ~ 254 mm (4.0 ~ 10.0")
		Length:	101.6 ~ 558.8 mm (4.0 ~ 22.0")
		Thickness:	0.07 ~ 0.09 mm (0.0028 ~ 0.0035") (Base)
ROLL PAPER			0.16 ~ 0.19 mm (0.0063 ~ 0.0075") (Total)
		Width:	216 mm (8.5")
		Length:	-
		Thickness:	0.07 ~ 0.09 mm (0.0028 ~ 0.0035")
PAPER FEEDING	STANDARD	Friction:	Rear in, Top out
		Push Tractor:	Rear in, Top out
		Pull Tractor:	Rear/Bottom in, Top out
	OPTIONAL	Cut Sheet Feeder:	Rear in, Top out
		Push-Pull Tractor:	Rear in, Top out
COPIES			Original + 3 copies
LINE SPACING			1/6 inch or programmable by 1/360 inch
INPUT DATA BUFFER			64 KByte
INTERFACE	STANDARD	Bi-directional parallel interface (IEEE-1284 nibble mode supported); Serial interface; USB interface (ver 1.1)	
RIBBON CARTRIDGE	STANDARD	FABRIC RIBBON CARTRIDGE (BLACK)	RIBBON LIFE: Approx. 2 million characters (LQ 10 CPI, 48 dots/character)
	OPTION	FABRIC RIBBON CARTRIDGE (COLOUR)	RIBBON LIFE: Black Approx. 1 million characters (LQ 10 CPI, 48dots/character)
			Magenta Approx. 0.7 million characters (LQ 10 CPI, 48 dots/character)
			Cyan Approx. 0.7 million characters (LQ 10 CPI, 48 dots/character)
			Yellow Approx. 0.5 million characters (LQ 10 CPI, 48 dots/character)
		FILM RIBBON CARTRIDGE (BLACK)	RIBBON LIFE: Approx. 0.2 million characters (LQ 10 CPI, 48 dots/character)
ACOUSTIC NOISE			Approx. 49dB (A) (ISO 7779 pattern)
RELIABILITY	MVBF (Mean Print Volume Between Failure)	12 million lines (Except print head)	
	MTBF (Mean Time Between Failure)	6000 POH (25% duty cycle)	
	PRINT HEAD LIFE	Approx. 200 million strokes/wire	
CONTROL PANEL			4 switches, 5 LEDs
ENVIRONMENTAL CONDITIONS (OPERATING)	TEMPERATURE	5 ~ 35 °C	
	HUMIDITY	10 ~ 80 % RH	
ELECTRICAL SPECIFICATIONS	RATED VOLTAGE	AC 120 V, AC 220 ~ 240 V	
	RATED FREQUENCY	50 ~ 60 Hz	
	POWER CONSUMPTION	Approx. 20 W (ISO/IEC 10561 Letter Pattern); ENERGY STAR compliant	
DIMENSIONS (D X W X H)			275 x 366 x 159mm
WEIGHT			Approx. 4.4 kg
PRINTER DRIVER /UTILITY	OS	Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0	
	UTILITY	Epson Status Monitor 3 (Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0 environment only)	

Epson is the registered trademark of SEIKO EPSON CORPORATION.

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON

EXCEED YOUR VISION

INDIA – (91) 80-305-15000, CALCUTTA – 228 31589/90,
CHENNAI – 302 77500, MUMBAI – 282 61515/16/17, NEW DELHI – 306 15000
INDONESIA – (62) 21-572-3161
MALAYSIA – (60) 3-562-88288
PHILIPPINES – (632) 813-6567
SINGAPORE – (65) 6586-5500, (65) 6586-3111
THAILAND / INDOCHINA – (662) 670-0680

Dealer's Stamp